



## Material Safety Data Sheet

---

SECTION I - Material Identity  
SECTION II - Manufacturer's Information  
SECTION III - Physical/Chemical Characteristics  
SECTION IV - Fire and Explosion Hazard Data  
SECTION V - Reactivity Data  
SECTION VI - Health Hazard Data  
SECTION VII - Precautions for Safe Handling and Use  
SECTION VIII - Control Measures  
SECTION IX - Label Data  
SECTION X - Transportation Data  
SECTION XI - Site Specific/Reporting Information  
SECTION XII - Ingredients/Identity Information

---

### SECTION I - Material Identity

---

Item Name	
Part Number/Trade Name	DANISH OIL FINISH
National Stock Number	8010L888983F
CAGE Code	51611
Part Number Indicator	A
MSDS Number	11497
HAZ Code	B

---

### SECTION II - Manufacturer's Information

---

Manufacturer Name	WATCO DENNIS CORPORATION
Street	19610 RANCHO WAY
City	RANCHO DOMINQUEZ
State	CA
Country	US
Zip Code	90220
Emergency Phone	213-635-2778

---

### MSDS Preparer's Information

---

Date MSDS Prepared/Revised 9/25/92  
 Active Indicator Y

### Alternate Vendors

---

### SECTION III - Physical/Chemical Characteristics

---

Appearance/Odor	ODOR-BLAND PAINT ODOR VARIOUS COLORS
Boiling Point	302-395 F
Vapor Pressure	4
Vapor Density	4.8
Specific Gravity	0.8691
Evaporation Rate	0.20
Solubility in Water	NIL
Container Pressure Code	4
Temperature Code	8
Product State Code	U

---

### SECTION IV - Fire and Explosion Hazard Data

---

Flash Point Method	TCC
Lower Explosion Limit	1.0
Upper Explosion Limit	6.7
Extinguishing Media	CO2, DRY CHEMICAL, FOAM, WATER SPRAY
Special Fire Fighting Procedures	DO NOT ENTER ANY ENCLOSED OR CONFINED SPACE WITHOUT PROTECTIVE EQUIP
Unusual Fire/Explosion Hazards	WATER SOAK OILY CLOTHY AFTER USE TO AVOID SPONTEOUS COMBUSTION

---

### SECTION V - Reactivity Data

---

Stability	YES
Stability Conditions to Avoid	OPEN FLAMES, HOT SURFACES OR ANY IGNITION SOURCES
Materials to Avoid	STRONG OXIDIZNG AGENTS
Hazardous Decomposition Products	NORMAL & INCOMPLETE COMBUSTION CAN PRODUCE TOXIC FUMES
Hazardous Polymerization	NO
Polymerization Conditions to Avoid	WILL NOT OCCUR

---

### SECTION VI - Health Hazard Data

---

Route of Entry: Skin	YES
Route of Entry: Ingestion	YES
Route of Entry: Inhalation	YES
Health Hazards - Acute and Chronic	CHRONIC EFFECTS:CHRONIC MIXED EXPOSURES TO SOLVENTS INCLUDING MINERAL SPIRITS CAN CAUSE PERSISTENT NEUROBEHAVIORAL SYMPTOMS SUCH AS FATIGUE,IRRITABILITY,SLEEP DISTURVANCES & DIFFICULTIES IN CONCENTRATION & MEMORY
Carcinogenity: NTP	NO
Carcinogenity: IARC	NO
Carcinogenity: OSHA	NO
Symptoms of Overexposure	SKIN:MAY BE ABSORBED THRU SKIN & MAY CAUSE SKIN IRRITATION. EYE:IRRITATING TO EYES,POSSIBLE REDNESS & BLURRED VISION. INHALATION:MAY CAUSE DIZZINESS,LIGHTHEADEDNESS & HEADACHES. INGESTION:MAY CAUSE GASTROINTESTINAL IRRITATION,NAUSEA & VOMITING
Medical Cond. Aggrevated by Exposure	N/R
Emergency/First Aid Procedures	SKIN:WASH W/SOAP & WATER. EYE:FLUSH W/WATER 15 MIN GET MEDICAL ATTENTION. INHALA

---

## SECTION VII - Precautions for Safe Handling and Use

---

Steps if Material Released/Spilled	ELIMINATE ALL SOURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPOR. CLEAN UP SPILLS AS SOON AS POSSILBE W/ABSORBENT CLAY DIATOMAEIOUS EARTH OR OTHER SUITABLE MATERIAL
Waste Disposal Method	PLACE ALL CONTAMINATED MATERIAL IN DISPOSABLE CONTAINERS & VURY IN APPROVED DUMPING AREA
Handling and Storage Precautions	KEEP AWAY FROM HEAT OR OPEN FLAME.KEEP OUT OF REACH OF CHILDREN. USE ONLY IN WELL VENTILATED AREAS. KEEP CONTAINER CLOSED WHEN NO IN USE. WATER SOAK

---

## SECTION VIII - Control Measures

---

Respiratory Protection	APPROVED RESPIRATOR FOR ORGANIC VAPOR OR MIST IF PPM REQUIRED
Ventilation	ADEQUATE FOR PPM
Protective Gloves	NEOPRENE
Eye Protection	CHEMICAL SAFETY GOGGLES IF NECESSARY
Other Protective Equipment	WASHING FACILITIES OFR EYES & SKIN SHOULD

Work Hygenic Practices

BE AVAILABLE NEARBY

AFTER USE, WASH HANDS THOROUGHLY W/SOAP &  
WATER. LAUNDER CONTAMINATED CLOTHING  
BEFORE RESUSE

---

 SECTION IX - Label Data
 

---

Protect Eye	YES
Protect Skin	YES
Protect Respiratory	YES
Chronic Indicator	YES
Contact Code	SLIGHT
Fire Code	UNKNOWN
Health Code	UNKNOWN
React Code	UNKNOWN

---

 SECTION X - Transportation Data
 

---

Container Quantity	1
Unit of Measure	GL

---

 SECTION XI - Site Specific/Reporting Information
 

---

Volatile Organic Compounds (P/G)	3.48
Volatile Organic Compounds (G/L)	417.0392

---

 SECTION XII - Ingredients/Identity Information
 

---

Ingredient #	01
Ingredient Name	MINERAL SPIRITS (PETROLEUM ALIPHATIC)
CAS Number	64742478
Proprietary	NO
Percent	0
OSHA PEL	SEE ADDITIONAL ING
Ingredient #	02
Ingredient Name	DANISH OIL FINISH (ALL COLORS)
CAS Number	1003
Proprietary	NO
Percent	44
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	03

Ingredient Name	SATIN WAX-NATURAL
CAS Number	1003
Proprietary	NO
Percent	91
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	04
Ingredient Name	SATIN OIL
CAS Number	1003
Proprietary	NO
Percent	81
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	05
Ingredient Name	TEAK OIL
CAS Number	1003
Proprietary	NO
Percent	44
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	06
Ingredient Name	WOOD FLOOR FINISH ( ALL COLORS)
CAS Number	1003
Proprietary	NO
Percent	34
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	07
Ingredient Name	REDWOOD FINISH
CAS Number	1003
Proprietary	NO
Percent	44
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	08
Ingredient Name	MARINE TEAKWOOD FINISH
CAS Number	1003
Proprietary	NO
Percent	44
OSHA PEL	500 PPM
ACGIH TLV	100 PPM
Ingredient #	09
Ingredient Name	TILE & BRICK SEALER
CAS Number	1003
Proprietary	NO

Percent	38
OSHA PEL	500 PPM
ACGIH TLV	100 PPM

---